

TABEL COMPARATIV POMPE DE SUPRAFATA

Specificatii/Articol	Pompa submersibila multietajata 4STM6-11, 1.1KW, 6.6 m³/h, H 75m	Pompa submersibila multietajata 4STM6-14, 1.5KW, 6.6 m³/h, H 105m	Pompa submersibila multietajata 4STM6-19, 2.2KW, 6.6 m³/h, H 135m
Debit	6.6 m ³ /h	6.6 m ³ /h	6.6 m ³ /h
Numar etaje	11	14	19
Diametrul orificiului de refulare	1 1/2" / 38.1 mm	1 1/2" / 38.1 mm	1 1/2" / 38.1 mm
Inaltime maxima de refulare	75 m	105 m	135 m
Temperatura maxima admisa lichid	40 °C	40 °C	40 °C
Clasa izolatie	B	B	B
Grad protectie	IP 68	IP 68	IP 68
Putere motor	1.1 kW	1.5 kW	2.2 kW
Tensiune de alimentare	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz
Diametru exterior pompa	4" / 100 mm	4" / 100 mm	4" / 100 mm
Lungime pompa	900 mm	1000 mm	1100 mm
Greutate	20 kg	22 kg	24 kg

