

### **TABEL COMPARATIV HIDROFOARE**

<b>Specificatii/Articol</b>	<b>Hidrofor ATJET100A, 0.75KW, 50l/min, 25l</b>	<b>Hidrofor ATSGJ600, 0.6KW,45l/min, 25l</b>	<b>Hidrofor ATSGJ800, 0.8KW, 50l/min, 25l</b>	<b>Hidrofor (de mare adancime) ATDP505A, 1.1KW, 150l/min, 25l</b>	<b>Hidrofor (de mare adancime) ATJDW/1A-2, 0.75KW, 130l/min, 25l</b>
<b>Adancimea maxima de aspiratie</b>	9 m	9 m	9 m	30 m	25 m
<b>Debit</b>	50 l/min	45 l/min	50 l/min	150 l/min	130 l/min
<b>Diametrul orificiului de aspiratie</b>	1 "	1 "	1 "	1.25" x 1"	1.25" x 1"
<b>Diametrul orificiului de refulare</b>	1 "	1 "	1 "	1 "	1 "
<b>Inaltime maxima de refulare</b>	40 m	39 m	46 m	36 m	25 m
<b>Volum butelie</b>	25 L	25 L	25 L	25 L	25 L
<b>Putere motor</b>	0.75 kW	0.6 kW	0.8 kW	1.1 kW	0.75 kW
<b>Tensiune de alimentare</b>	230 V	230 V	230 V	230 V	230 V