

TABEL COMPARATIV MOTOPOMPE

Specificatii/Articol	Motopompa apa curata 2" ROMP50ZB26, 7CP, 533L/min, H 8m/30m	Motopompa apa curata 3" ROMP80ZB30, 7CP, 967L/min, H 8m/30m	Motopompa presiune 2" ROMP50ZB60 / 7CP, 533L/min, H 8m/65m	Motopompa apa murdara 3" ROMP80WG, 7CP, 967L/min, H 8m/26m
Debit maxim	533 l/min	967 l/min	533 l/min	967 l/min
Diametru aspiratie	50 mm / 2"	80 mm / 3"	50 mm / 2"	80 mm / 3"
Diametru refulare	50 mm / 2"	80 mm / 3"	1 x 50 mm / 2", 2 x 38 mm / 1.5"	80 mm / 3"
Inaltime absortie	8 m	8 m	8 m	8 m
Inaltime refulare	30 m	30 m	65 m	26 m
Timp amorsare	< 180 sec	< 150 sec	< 180 sec	< 150 sec
Aprindere motor	Bobina de inductie	Bobina de inductie	Bobina de inductie	Bobina de inductie
Capacitate combustibil	3.6 l	3.6 l	3.6 l	3.6 l
Capacitate ulei motor	0.6 l	0.6 l	0.6 l	0.6 l
Consum combustibil	≤395 g / kW / ora	≤395 g / kW / ora	≤395 g / kW / ora	≤395 g / kW / ora
Dimensiuni motor (LxIxh)	405 x 365 x 375 mm	405 x 365 x 375 mm	405 x 365 x 375 mm	405 x 365 x 375 mm
Filtru aer motor	Uscat, cu dublu element de filtrare	Uscat, cu dublu element de filtrare	Uscat, cu dublu element de filtrare	Uscat, cu dublu element de filtrare
Greutate motor	16 kg	16 kg	16 kg	16 kg
Numar cilindri motor	1 cilindru	1 cilindru	1 cilindru	1 cilindru
Racire motor	Racit fortat cu aer	Racit fortat cu aer	Racit fortat cu aer	Racit fortat cu aer
Sistem de ungere motor	Barbotaj	Barbotaj	Barbotaj	Barbotaj
Model motor	170F	170F	170F	170F
Tip motor	4 timpi, OHV, inclinat 25°	4 timpi, OHV, inclinat 25°	4 timpi, OHV, inclinat 25°	4 timpi, OHV, inclinat 25°
Putere maxima motor	7.0 CP	7.0 CP	7.0 CP	7.0 CP
Capacitate cilindrica	212 cmc	212 cmc	212 cmc	212 cmc
Diametru / Cursa piston	70 / 55 mm	70 / 55 mm	70 / 55 mm	70 / 55 mm
Dimensiune ambalat (LxIxh)	470 x 370 x 380 mm	500 x 370 x 450 mm	470 x 370 x 380 mm	565 x 445 x 425 mm
Greutate	24 kg	28 kg	32 kg	38 kg